LONGi


Hi-MO X10 Scientist

LR7-54HVD(Dual Glass for Australia Market)

475~495M (243W/m²)

First Choice For High-End Residential

- **Extreme Efficiency, 24.3%+**
- **High Power Generation**
  Leading HPBC2.0 technology, more power generation under the same area
- **Low Carbon and Environmentally Friendly**
  Low carbon for the whole lifecycle process, more environmentally friendly
- **Safety Function**
  Anti-Shading and Prevent Localized Overheating



25 **25-Year Warranty for Materials and Processing**

30 **30-Year Warranty for Extra Front Side Linear Power Output**

Complete System and Product Certifications

IEC61215, IEC 61730
ISO9001: Quality Management System
ISO14001: Environment Management System
ISO45001: Occupational Health and Safety Management System
IEC62941: Quality System for PV Module Manufacturing


TUV SUD


Residential PV Modules, Choose BC


LR7-54HVD 475~495M

24.3%	0~3%	<1%	0.35%	BC-CELL
MAX MODULE EFFICIENCY	POWER BINNING TOLERACE	FIRST YEAR POWER DEGRADATION	YEAR 2-30 POWER DEGRADATION	LOWER OPERATING TEMPERATURE

Additional Value








Mechanical Parameters

Cell Orientation	108 (6×18)
Junction Box	IP68
Output Cable	4mm², +400, -200mm/±1200mm length can be customized
Glass	2.0mm semi-tempered glass+1.6mm semi-tempered glass
Frame	Black anodized aluminum alloy frame
Weight	23.5kg
Dimension	1800×1134×30mm
Packaging	36pcs per pallet / 216pcs per 20' GP / 864pcs per 40' HC
Connector	PV-LR5(Longi) PV-KST4-EVO2A/xy_UR, PV-KBT4-EVO2A/xy_UR(Stäubli)



Electrical Characteristics

STC : AM1.5 1000W/m² 25°C Test uncertainty for Pmax: ±3% Voc& Isc: ±5% BSI Bificiality: φPmax 70±5%, φVoc 98%±5%, φIsc 70±5%

Module Type	LR7-54HVD-475M	LR7-54HVD-480M	LR7-54HVD-485M	LR7-54HVD-490M	LR7-54HVD-495M
Testing Condition	STC	STC	STC	STC	STC
Maximum Power (Pmax/W)	475	480	485	490	495
Open Circuit Voltage (Voc/V)	40.42	40.53	40.64	40.75	40.86
Short Circuit Current (Isc/A)	14.88	14.98	15.08	15.18	15.28
Voltage at Maximum Power (Vmp/V)	33.40	33.51	33.62	33.73	33.84
Current at Maximum Power (Imp/A)	14.23	14.33	14.43	14.53	14.63
Module Efficiency(%)	23.3	23.5	23.8	24.0	24.3
BSI Short Circuit Current (A)	17.9	18.11	18.24	18.36	18.48

Electrical Characteristics

BNPI : Irradiance:friont 1000/m² rear 135W/m² 25°C AM1.5 BSI: Friont 1000/m² rear 300 W/m² 25°C AM1.5

Module Type	LR7-54HVD-475M	LR7-54HVD-480M	LR7-54HVD-485M	LR7-54HVD-490M	LR7-54HVD-495M
Testing Condition	BNPI	BNPI	BNPI	BNPI	BNPI
Maximum Power (Pmax/W)	520	526	531	537	542
Open Circuit Voltage (Voc/V)	40.42	40.53	40.64	40.75	40.86
Short Circuit Current (Isc/A)	16.28	16.40	16.51	16.62	16.73
Voltage at Maximum Power (Vmp/V)	33.40	33.51	33.62	33.73	33.84
Current at Maximum Power (Imp/A)	15.57	15.68	15.80	15.91	16.02
Module Efficiency(%)	25.5	25.7	26.0	26.3	26.6

Operating Parameters

Module[T98] Max	+70°C
Power Binning Tolerance	0 ~ 3%
Maximum System Voltage	DC1500V (IEC)
Maximum Series Fuse Rating	30A
Nominal Operating Cell Temperature	45±2°C
Protection Class	Class II
Bifaciality φPmax	70±5%
Fire Rating	IEC Class C
Power Measurement Tolerance:	±3%

Mechanical Loading

Front Side Maximum Static Loading	+5400Pa
Rear Side Maximum Static Loading	-2400Pa
Hailstone Test	25mm Hailstone at the speed of 23m/s

Temperature Ratings (STC)

Temperature Coefficient of Isc	+0.050%/°C
Temperature Coefficient of Voc	-0.200%/°C
Temperature Coefficient of Pmax	-0.260%/°C

Importer: LONGi Solar Australia Pty Ltd
Add: Level 17, 570 George Street, Sydney NSW 2000
Tel: 1800 328 888
Email: au@longi.com
ABN: 15 632 322 288
Website: www.longi.com/au

Manufacturer: LONGi Green Energy Technology Co.,Ltd.
Add: No.388,Middle Hangtian Road, Chang'an District, Xi'an, Shaanxi 710100,P.R.China.
Website: www.longi.com
Tel: (+86)400-860-1012
Email: market@ongi.com

Specifications included in this datasheet are subject to change without notice. LONGi reserves the right of final interpretation. (Australia and New Zealand Only)

Made in China