Hi-MO X10 Scientist

LR7-60HVH

535~560M

- More flexible installation methods, suitable for short frame clamps mounting with high mechanical loading
- High efficiency with better energy generation performance
- N-type TaiRay wafer & HPBC 2.0 innovative technology enhances high product reliability

25 25-year Warranty for Materials and Processing

30 30-year Warranty for Extra Linear Power Output



Complete System and Product Certifications

IEC 61215, IEC 61730

ISO9001:2015: ISO Quality Management System

ISO14001: 2015: ISO Environment Management System

ISO45001: 2018: Occupational Health and Safety

IEC62941: Guideline for module design qualification and type approval

LONGi


TUV SUD


Hi-MO X10 Scientist


LR7-60HVH 535~560M


24.8%	0~3%	<1%	0.35%	BC-CELL
MAX MODULE EFFICIENCY	POWER BINNING TOLERANCE	FIRST YEAR POWER DEGRADATION	YEAR 2-30 POWER DEGRADATION	LOWER OPERATING TEMPERATURE

Additional Value









Mechanical Parameters

Cell Orientation	120 (6×20)
Junction Box	IP68, three diodes
Output Cable	4mm², +400, -200mm/±1400mm length can be customized
Glass	Single glass 3.2mm coated tempered glass
Frame	Anodized aluminum alloy frame
Weight	25kg
Dimension	1990×1134×30mm
Packaging	36pcs per pallet / 180pcs per 20'GP / 792pcs per 40' HC
Connector	PV-LR5(Longi) PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy (Stäubli)

Electrical Characteristics

STC : AM1.5 1000W/m2 25°C NOCT : AM1.5 800W/m2 20°C 1m/s LRC: 200±2W/m² 25±2°C

Module Type	LR7-60HVH-535M			LR7-60HVH-540M			LR7-60HVH-545M			LR7-60HVH-550M			LR7-60HVH-555M			LR7-60HVH-560M		
Testing Condition	STC	NOCT	LRC	STC	NOCT	LRC	STC	NOCT	LRC	STC	NOCT	LRC	STC	NOCT	LRC	STC	NOCT	LRC
Maximum Power (Pmax/W)	535	407	102	540	411	103	545	415	104	550	419	105	555	422	106	560	426	107
Open Circuit Voltage (Voc/V)	44.78	42.57	41.26	44.88	42.66	41.35	44.98	42.76	41.43	45.08	42.85	41.52	45.18	42.95	41.60	45.28	43.04	41.69
Short Circuit Current (Isc/A)	15.15	12.17	3.03	15.25	12.25	3.05	15.35	12.33	3.07	15.45	12.41	3.09	15.55	12.49	3.11	15.65	12.57	3.13
Voltage at Maximum Power (Vmp/V)	37.01	35.16	34.02	37.11	35.26	34.11	37.21	35.35	34.20	37.31	35.45	34.29	37.41	35.54	34.38	37.51	35.64	34.47
Current at Maximum Power (Imp/A)	14.46	11.58	2.99	14.55	11.66	3.01	14.65	11.73	3.03	14.74	11.81	3.05	14.84	11.89	3.07	14.93	11.96	3.09
Module Efficiency(%)	23.7			23.9			24.2			24.4			24.6			24.8		

Test uncertainty for Pmax:±3% Voc & Isc: ±5%

Operating Parameters

Module[T98] Max	+70°C
Power Binning Tolerance	0 ~ 3%
Maximum System Voltage	DC1500V (IEC)
Maximum Series Fuse Rating	25A
Nominal Operating Cell Temperature	45±2°C
Protection Class	Class II
Fire Rating	IEC Class C
Power Measurement Tolerance:	±3%

Mechanical Loading

Front Side Maximum Static	+5400Pa
Loading Rear Side Maximum	-2400Pa
Static Loading Hailstone Test	25mm Hailstone at the speed of 23m/s

Temperature Ratings (STC)

Temperature Coefficient of Isc	+0.050%/°C
Temperature Coefficient of Voc	-0.200%/°C
Temperature Coefficient of Pmax	-0.260%/°C

LONGi

Importer: LONGi Solar Australia Pty Ltd
Add: Level 17, 570 George Street, Sydney NSW 2000
Tel: 1800 328 888
Email: au@longi.com
ABN: 15 632 322 288
Website: www.longi.com/au

Manufacturer: LONGi Green Energy Technology Co.,Ltd.
Add: No.388,Middle Hangtian Road, Chang'an District, Xi'an, Shaanxi 710100,P.R.China.
Website: www.longi.com
Tel: (+86)400-860-1012
Email: market@longi.com

Specifications included in this datasheet are subject to change without notice. LONGi reserves the right of final interpretation. (Australia and New Zealand Only)

Made in China